

AUDI (EU) A6, S6, RS 6 4B A6 2.8 V6 30V (1997-2000)



MOTOR ACK, AHA, ALG, AMX, APR, AQD
Kapasitet: 5,5 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Bytt hver 15000 km/ 12 måneder

BRUK	KLIMA
Normal	Kaldt

PRODUKTANBEFALING 1		
Presteza MSP 5W-30		

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL CVT
Kapasitet: 1,3 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1071		

DIFFERENSIAL FRA AUTOMAT
Kapasitet: 0,8 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Sjekk hver 60000 km

GIR AUTOMAT 01V 5/1
Kapasitet: 9 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4026	SP Matic 2032	

Sjekk hver 30000 km

AUDI (EU) A6, S6, RS 6 4B A6 2.8 V6 30V (1997-2000)



TRANSAKSEL CVT 01J 1/1

Kapasitet: 5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4016

TRANSAKSEL MANUELL 012 / 01W / 0A9 5/1

Kapasitet: 2,25 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 30000 km

HYDRAULISK BREMSESYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Bytt hver 24 måneder

SERVOSTYRING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KJØLESYSTEM

Kapasitet: 6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.