

AUDI (EU) A6, S6, RS 6 4B A6 4.2 V8 40V QUATTRO (2000-2005)



MOTOR ARS, ASG Kapasitet: 7,5 liter

BRUK		KLIMA
Utvidet tømning (maks)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Bytt hver 30000 km/ 24 måneder

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Bytt hver 15000 km/ 12 måneder

BRUK		KLIMA
Normal		Kaldt
PRODUKTANBEFALING 1		
Presteza MSP 5W-30		

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL BAK Kapasitet: 1,5 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		

Sjekk hver 30000 km

DIFFERENSIAL FRA AUTOMAT Kapasitet: 1,3 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Sjekk hver 60000 km

AUDI (EU) A6, S6, RS 6 4B A6 4.2 V8 40V QUATTRO (2000-2005)

**GIR AUTOMAT 01L 5/1**

Kapasitet: 9,8 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

PRODUKTANBEFALING 2

SP Matic 2032*Sjekk hver 30000 km***OVERFØRINGSBOKS FRA AUTOMATISK**

Kapasitet: 0,9 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90**HYDRAULISK BREMSESYSTEM**

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Bytt hver 24 måneder***SERVOSTYRING**

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013**KJØLESYSTEM**

Kapasitet: 11 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.