



MOTOR BDW

Kapasitet: 6,5 liter (Servicepåfylling)

BRUK		KLIMA
Utvidet tømning (maks)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Bytt hver 30000 km/ 24 måneder

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Bytt hver 15000 km/ 12 måneder

BRUK		KLIMA
Normal		Kaldt
PRODUKTANBEFALING 1		
Presteza MSP 5W-30		

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL CVT

Kapasitet: 1,3 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Gear 1071		

Sjekk hver 24 måneder/ 30000 km

TRANSAKSEL CVT Multitronic

Kapasitet: 7,5 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 4016		

Bytt hver 60000 km

**TRANSAXSEL MANUELL 01X 6/1**

Kapasitet: 3 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1**SP Gear 1011****PRODUKTANBEFALING 2****Syngear TDL 75W-90***Sjekk hver 30000 km***HYDRAULISK BREMSE-/CLUTCH-SYSTEM****BRUK**

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1**Drauliquid-LV Super DOT 4***Bytt hver 24 måneder***SERVOSTYRING****BRUK**

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1**SP Fluid 3013****KJØLESYSTEM**

Kapasitet: 12 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1**Coolant SP 12 EVO**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.