ACURA (USA / CAN) MDX YD3/YD4 MDX 3.0 SPORT HYBRID (CAN) (2017-2020)



ENGINE JNA2 Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1			
Presteza MSP 0W-20			
Champio aver (1) manths			

Change every 12 months

DIFFERENTIAL REAR Twin Motor Unit Capacity: 2,42 liter			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Change every 24000 km			

USE	CLIMATE
Initial service, severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 12000 km	·

0 ,		
USE		CLIMATE
Flexible (on board maintenance syste	em)	Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

ACURA (USA / CAN) MDX YD3/YD4 MDX 3.0 SPORT HYBRID (CAN) (2017-2020)



TRANSMISSION AUTOMATIC DCT 7/1 Capacity: 3,5 liter (Service fill)			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Change every 40000 km			
USE		CLIMATE	
Severe, first change only		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Change every 48000 km			
USE		CLIMATE	
Flexible (on board maintenance systemeters)	em)	Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Change every 36 months			

COOLING SYSTEM Capacity: 7,68 liter (Total)		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

COOLING SYSTEM INVERTER Capacity: 0,41 liter (Expansion tank), Capacity: 1,67 liter (Total)		
USE		CLIMATE
Flexible (on board maintenance syste	em)	Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

ACURA (USA / CAN) MDX YD3/YD4 MDX 3.0 SPORT HYBRID (CAN) (2017-2020)



AIRCONDITIONING COMPRESSOR

Capacity: 140-155 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 675-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.