PRODUCT RECOMMENDATION

ACURA (USA / CAN) TL UA4, UA5 TL 3.2 (USA) (2002-2003)

ENGINE J32A1
Capacity: 4,4 liter, Capacity: 5 liter (Dry fill), Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Change every 12000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Change every 6000 km/ 6 months

TRANSAXLE AUTOMATIC 5/1
Capacity: 7,2 liter (Dry fill), Capacity: 2,9 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 144000 km/ 60 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 48000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 192000 km/ 72 months

USE		CLIMATE
First change only, severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 96000 km/ 36 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ACURA (USA / CAN) TL UA4, UA5 TL 3.2 (USA) (2002-2003)

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Check every 1 months, change every 36 months

POWER STEERING
Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM
Capacity: 7,5 liter (Dry fill), Capacity: 5,6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 96000 km/ 60 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 192000 km/ 120 months

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367