ACURA (USA / CAN) TL UA8, UA9 TL 3.7 SH-AWD (2011-2012)



ENGINE J37A4 Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service fill)			
use Flexible (on board maintenance syst	em)	CLIMATE Moderate	
PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20			

DIFFERENTIAL REAR Capacity: 2,5-2,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSFERBOX Capacity: 0,4-0,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90		

TRANSMISSION AUTOMATIC 5/1 Capacity: 7,7 liter (Dry fill), Capacity: 2,8 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			

TRANSMISSION MANUAL 6/1 Capacity: 2,5 liter (Dry fill), Capacity: 2,1 liter (Service fill)			
use Normal		CLIMATE Moderate	
PRODUCT RECOMMENDATION 1 SP Gear 5015			

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

PRODUCT RECOMMENDATION

ACURA (USA / CAN) TL UA8, UA9 TL 3.7 SH-AWD (2011-2012)



COOLING SYSTEM Capacity: 8,3 liter (Dry fill), Capacity: 6,3 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
PRODUCT RECOMMENDATION 1		Moderate	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.