

# ARO 24 24 2.5 (1984-2006)



**ENGINE** Aro L25  
Capacity: 5,6 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Bi-Turbo 15W-40</b>   | <b>Bi-Turbo 20W-50</b>   |               |

*Change every 5000 km*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    |          |

*Change every 5000 km*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 1 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Gearlube GL-5 80W-90</b> |  |          |

*Change every 30000 km/ 36 months*

**DIFFERENTIAL REAR**  
Capacity: 1,7 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Gearlube GL-5 80W-90</b> |  |          |

*Change every 30000 km/ 36 months*

**TRANSFERBOX**  
Capacity: 1,25 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Gearlube GL-5 80W-90</b> |  |          |

*Change every 30000 km/ 36 months*

**ARO 24 24 2.5 (1984-2006)****TRANSMISSION MANUAL 4/1**

Capacity: 2,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Change every 30000 km/ 36 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,75 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 20000 km/ 24 months***POWER STEERING**

Capacity: 3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**ATF-A***Change every 50000 km***COOLING SYSTEM**

Capacity: 13,25 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Change every 20000 km/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.