

# ASTON MARTIN V8 VANTAGE V8 VANTAGE

## (2012-2013)

**ENGINE**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Emperol 5W-50</b>	<b>Emperol Racing 10W-60</b>	

*Change every 16000 km/ 12 months***TRANSAXLE MANUAL** Graziano 6/1

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

*Check every 32000 km/ 24 months, change every 64000 km/ 48 months***TRANSAXLE SEMI-AUTOMATIC** Graziano SportShift II 7/1

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

*Check every 32000 km/ 24 months, change every 64000 km/ 48 months***HYDRAULIC ACTUATION GEARBOX/CLUTCH**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

*Check every 16000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

*Check every 16000 km/ 12 months, change every 24 months*

# ASTON MARTIN V8 VANTAGE V8 VANTAGE

## (2012-2013)



### POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

Check every 16000 km/ 12 months

### COOLING SYSTEM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 16000 km/ 12 months, change every 160000 km/ 60 months

### AIRCONDITIONING

Capacity: 750 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*