

AUDI (EU) A5, S5, RS 5 8T A5 2.0 TFSI (165 KW) (2013-2016)



ENGINE CNCD
Capacity: 4,6 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 15000 km/ 12 months

DIFFERENTIAL CVT
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

TRANSAXLE MANUAL 0B1 6/1
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

Check every 24 months/ 30000 km

TRANSMISSION CVT 0AW 1/1
Capacity: 8 liter (Dry fill), Capacity: 5,5-6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4016

Change every 60000 km

AUDI (EU) A5, S5, RS 5 8T A5 2.0 TFSI (165 KW) (2013-2016)**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months***COOLING SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.