

AUDI (EU) A6, S6 4A A6 2.5 TDI QUATTRO (103 KW) (1995-1997)

**ENGINE**

Capacity: 5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 2

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 3

Specialsynth MSP 5W-40*Change every 15000 km/ 12 months*

USE

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

Emperol 5W-40*Change every 15000 km/ 12 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 15000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 15000 km/ 12 months***TRANSAXLE MANUAL 6/1**

Capacity: 2,35 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 15000 km/ 12 months*

AUDI (EU) A6, S6 4A A6 2.5 TDI QUATTRO (103 KW) (1995-1997)


TRANSAXLE MANUAL/TRANSFERBOX 6/1

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 15000 km/ 12 months

TRANSMISSION AUTOMATIC 4/1

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 30000 km/ 12 months, change every 60000 km/ 48 months

HYDRAULIC SYSTEM POWER STEERING/LEVELLING

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

POWER STEERING

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

PRODUCT RECOMMENDATION

AUDI (EU) A6, S6 4A A6 2.5 TDI QUATTRO (103 KW) (1995-1997)



COOLING SYSTEM

Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.