PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 430 CPDS

ENGINE Perkins 4.236 Capacity: 12 liter		
USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 **Dieselfleet CD+ 15W-40**	PRODUCT RECOMMENDATION 2 **Multifleet SHPD 15W-40**	
Change every 150 hours		

DIFFERENTIAL + OIL IMMERSED BRAKES REAR Hurth Capacity: 7,5 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 900 hours		

DIFFERENTIAL FRONT Hurth Capacity: 8,5 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 900 hours		

HUB REDUCTIONS FRONT Capacity: 1 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 900 hours		

HUB REDUCTIONS REAR Capacity: 1 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 900 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 430 CPDS

TRANSMISSION Clark 18000
Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	**ATF Dexron II-D**	

Change every 900 hours

HYDRAULIC SYSTEM
Capacity: 100 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 900 hours

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 15,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 430 CPDS

HYDRAULIC INCHING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

TELESCOPIC BOOM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367