

MANITOU GAFFELTRUCKER MSI MSI 25 G BUGGIE TOYOTA 4Y (<-139125) (INNTIL 2001)



MOTOR Toyota 4Y
Kapasitet: 4 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

AKSELSVINGNING BAK

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

NAVREDUKSJONER FORAN

Kapasitet: 1,1 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

HYDRAULIKKSYSTEM

Kapasitet: 95 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

FETTPUNKTER/NIPLER MASTELEDD

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2

Caliplex HD Grease EP 2

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2

MANITOU GAFFELTRUCKER MSI MSI 25 G BUGGIE TOYOTA 4Y (<-139125) (INNTIL 2001)



FETTPUNKTER/NIPLER VIPPESYLINDERFOT

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

SMØREPUNKTER/NIPLER ANNET

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KJØLESYSTEM

Kapasitet: 11 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.