

MANITOU GAFFELTRUCKER MSI MSI 25 TURBO BUGGIE SERIES 1-E2 PERKINS 404C-22T (2004-2008)



MOTOR Perkins 404C-22T
Kapasitet: 9,75 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Sjekk hver 8 timer, bytt hver 12 måneder/ 500 timer

AKSELSVINGNING BAK

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Bytt hver 50 timer

NAVREDUKSJONER FORAN Brevini CWD 2050/1M
Kapasitet: 1 liter (hver)

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Sjekk hver 50 timer, bytt hver 2000 timer/ 24 måneder

HYDRAULIKKSYSTEM

Kapasitet: 95 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Sjekk hver 50 timer, bytt hver 1000 timer/ 12 måneder

FETTPUNKTER/NIPLER MAST

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

Bytt hver 50 timer

MANITOU GAFFELTRUCKER MSI MSI 25 TURBO BUGGIE SERIES 1-E2 PERKINS 404C-22T (2004-2008)



SMØREPUNKTER/NIPLER ANNET

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Bytt hver 50 timer

KJØLESYSTEM

Kapasitet: 10,5 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Sjekk hver 8 timer, bytt hver 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.