

MANITOU GAFFELTRUCKER MSI MSI 25 TURBO SERIES 2-E3 KUBOTA V2403M-T- E3B (2008 OG ETTER)



MOTOR Kubota V2403-M-DI-T-E3B
Kapasitet: 10 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Sjekk hver 10 timer, bytt hver 500 timer/ 6 måneder

AKSELSVINGNING BAK

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

NAVREDUKSJONER FORAN

Kapasitet: 1 liter (hvert nav)

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Sjekk hver 50 timer, bytt hver 2000 timer/ 24 måneder

BRUK		KLIMA
Første service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Bytt hver 50 timer

HYDRAULIKKSYSTEM

Kapasitet: 95 liter (Hydraulikk tank)

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Sjekk hver 50 timer, bytt hver 1000 timer/ 12 måneder

MANITOU GAFFELTRUCKER MSI MSI 25 TURBO SERIES 2-E3 KUBOTA V2403M-T- E3B (2008 OG ETTER)



FETTPUNKTER/NIPLER MAST

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KJØLESYSTEM

Kapasitet: 10 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Sjekk hver 50 timer, bytt hver 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.