

MANITOU GAFFELTRUCKER MSI MSI 30 D BUGGIE PERKINS 903-27 (<-139125) (1997-2002)



MOTOR Perkins 903-27
Kapasitet: 5 liter

BRUK
Normal

KLIMA
Fra Middelhavet

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Sjekk hver 10 timer, bytt hver 400 timer/ 12 måneder

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Armado Synth 5W-30

Sjekk hver 10 timer, bytt hver 400 timer/ 12 måneder

BRUK
Første service

KLIMA
Fra Middelhavet

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Bytt hver 50 timer

BRUK
Første service

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Armado Synth 5W-30

Bytt hver 50 timer

NAVREDUKSJONER FORAN
Kapasitet: 1,1 liter (hver)

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Sjekk hver 50 timer, bytt hver 12 måneder/ 2400 timer

HYDRAULIKKSYSTEM
Kapasitet: 95 liter (Hydraulikktank)

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

Sjekk hver 50 timer, bytt hver 800 timer/ 12 måneder

MANITOU GAFFELTRUCKER MSI MSI 30 D BUGGIE PERKINS 903-27 (<-139125) (1997- 2002)



SMØREPUNKTER/NIPLER GENERELLE

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KJØLESYSTEM

Kapasitet: 11 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Sjekk hver 10 timer, bytt hver 800 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.