

MANITOU MANISKOPISK MLT MLT 630 TURBO MONO-ULTRA SERIE 3



MOTOR

Kapasitet: 7,6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Bytt hver 400 timer

BRUK

Første service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Bytt hver 50 timer

AKSELSVINGNING BAK

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

DIFFERENSIAL BAK

Kapasitet: 8,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Bytt hver 800 timer

DIFFERENSIAL FORAN

Kapasitet: 8,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Bytt hver 800 timer

MANITOU MANISKOPISK MLT MLT 630 TURBO MONO-ULTRA SERIE 3



NAVREDUKSJONER BAK

Kapasitet: 0,6 liter (hvert nav)

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Bytt hver 800 timer

NAVREDUKSJONER FORAN

Kapasitet: 0,6 liter (hvert nav)

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Bytt hver 800 timer

OVERFØRING

Kapasitet: 8,5 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Almirol		

Bytt hver 800 timer

OVERFØRINGSBOKS

Kapasitet: 0,6 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Bytt hver 800 timer

HYDRAULIKKSYSTEM

Kapasitet: 118 liter (Hydraulikktank)

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Bytt hver 800 timer

MANITOU MANISKOPISK MLT MLT 630

TURBO MONO-ULTRA SERIE 3



HYDRAULISK BREMSESYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

SMØREPUNKTER/NIPLER

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KJØLESYSTEM

Kapasitet: 15 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

GLIDEPUTER TVERRSTOPPER

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.