

# MANITOU MANISKOPISK MLT MLT 725 ULTRA SERIE 3



## MOTOR

Kapasitet: 7,6 liter

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

#### PRODUKTANBEFALING 2

**Dieselfleet CD+ 15W-40**

#### PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

Bytt hver 400 timer

### BRUK

Første service

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

#### PRODUKTANBEFALING 2

**Dieselfleet CD+ 15W-40**

#### PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

Bytt hver 50 timer

## AKSELSVINGNING BAK

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Labora Grease**

#### PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

#### PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

## DIFFERENSIAL BAK

Kapasitet: 8,5 liter

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

#### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

Bytt hver 800 timer

## DIFFERENSIAL FORAN

Kapasitet: 8,5 liter

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agrifluid HT**

Bytt hver 800 timer

# MANITOU MANISKOPISK MLT MLT 725

## ULTRA SERIE 3



### NAVREDUKSJONER BAK

Kapasitet: 0,6 liter (hvert nav)

#### BRUK

Normal

#### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

#### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Bytt hver 800 timer*

### NAVREDUKSJONER FORAN

Kapasitet: 0,6 liter (hvert nav)

#### BRUK

Normal

#### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

#### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Bytt hver 800 timer*

### OVERFØRING

Kapasitet: 8,5 liter

#### BRUK

Normal

#### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**ATF Almirol**

*Bytt hver 800 timer*

### OVERFØRINGSBOKS

Kapasitet: 0,6 liter

#### BRUK

Normal

#### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

#### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Bytt hver 800 timer*

### HYDRAULIKKSYSTEM

Kapasitet: 118 liter (Hydraulikktank)

#### BRUK

Normal

#### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Perlus H 46**

*Bytt hver 800 timer*

# MANITOU MANISKOPIISK MLT MLT 725

## ULTRA SERIE 3



### HYDRAULISK BREMSESYSTEM

| BRUK                |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Moderat |
| PRODUKTANBEFALING 1 |  |         |
| <b>LHM +</b>        |  |         |

### SMØREPUNKTER/NIPLER

| BRUK                 |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

### KJØLESYSTEM

Kapasitet: 15 liter

| BRUK                  |                      | KLIMA                         |
|-----------------------|----------------------|-------------------------------|
| Normal                |                      | Moderat                       |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3           |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> | <b>Coolant -38 Organic NF</b> |

### GLIDEPUTER TVERRSTOPPER

| BRUK                 |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.