

MANITOU MANISKOPISK MLT MLT 845-120

LSU SERIE 3-E2



MOTOR

Kapasitet: 11 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Bytt hver 400 timer

BRUK

Første service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Bytt hver 50 timer

DIFFERENSIAL BAK

Kapasitet: 7,25-7,3 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Bytt hver 800 timer

DIFFERENSIAL FORAN

Kapasitet: 6,7-7,2 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Bytt hver 800 timer

NAVREDUKSJONER BAK

Kapasitet: 0,75-1,8 liter (hvert nav)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Bytt hver 800 timer

MANITOU MANISKOPISK MLT MLT 845-120

LSU SERIE 3-E2



NAVREDUKSJONER FORAN

Kapasitet: 0,75-1,8 liter (hvert nav)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Bytt hver 800 timer

OVERFØRING

Kapasitet: 15,1 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Bytt hver 800 timer

VINKELTANNHJULBOKS

Kapasitet: 2,2 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Bytt hver 800 timer

HYDRAULIKKSYSTEM

Kapasitet: 131 liter (Hydraulikktank)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Bytt hver 800 timer

HYDRAULISK BREMSESYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

MANITOU MANISKOPISK MLT MLT 845-120

LSU SERIE 3-E2



SMØREPUNKTER/NIPLER

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

KJØLESYSTEM

Kapasitet: 18,5 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.