

MANITOU MANISKOPISK MT/MTA MT 222 CP TURBO



MOTOR Perkins T4.236
Kapasitet: 8 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Bytt hver 400 timer

BRUK	KLIMA
Første service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Bytt hver 50 timer

DIFFERENSIAL FORAN Hurth
Kapasitet: 31,8 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Bytt hver 800 timer

NAVREDUKSJONER FORAN
Kapasitet: 1,1 liter (hvert nav)

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Bytt hver 800 timer

OVERFØRING Borg Warner
Kapasitet: 8,5 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

Bytt hver 800 timer

MANITOU MANISKOPISK MT/MTA MT 222

CP TURBO



HYDRAULIKKSYSTEM

Kapasitet: 110 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Bytt hver 800 timer

HYDRAULISK BREMSESYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

SMØREPUNKTER/NIPLER

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KJØLESYSTEM

Kapasitet: 15 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

TELESKOPBOM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.