

MANITOU MANISKOPISK MT/MTA MT 450 CP



MOTOR Perkins T4.236
Kapasitet: 9 liter

BRUK
Normal

KLIMA
Fra Middelhavet

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Bytt hver 150 timer

DIFFERENSIAL BAK
Kapasitet: 15 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Bytt hver 900 timer

DIFFERENSIAL FORAN
Kapasitet: 15 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Bytt hver 900 timer

NAVREDUKSJONER BAK
Kapasitet: 1 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Bytt hver 900 timer

NAVREDUKSJONER FORAN
Kapasitet: 1 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Bytt hver 900 timer

MANITOU MANISKOPISK MT/MTA MT 450 CP



OVERFØRING Clark 18000
Kapasitet: 18 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

Bytt hver 900 timer

HYDRAULIKSYSTEM
Kapasitet: 180 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Bytt hver 900 timer

HYDRAULISK BREMSESYSTEM

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

SMØREPUNKTER/NIPLER

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KJØLESYSTEM

Kapasitet: 17,5 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

MANITOU MANISKOPISK MT/MTA MT 450 CP



HYDRAULISK LANGSOMTGÅENDE SYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

TELESKOPBOM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.