

MANITOU MANISKOPISK MT/MTA MT 830 S CUMMINS



MOTOR Cummins 4B3.9T, 4B3.9

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Bytt hver 300 timer

BRUK	KLIMA
Første service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Bytt hver 50 timer

AKSELLEDD MED WIELAND-BØSSINGER

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

DIFFERENSIAL BAK

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Bytt hver 900 timer

DIFFERENSIAL FORAN Hurth

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Bytt hver 900 timer

MANITOU MANISKOPISK MT/MTA MT 830 S CUMMINS



NAVREDUKSJONER BAK

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Bytt hver 900 timer

NAVREDUKSJONER FORAN

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Bytt hver 900 timer

OVERFØRING Spicer Compact Shuttle

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

Bytt hver 900 timer

HYDRAULIKKSYSTEM

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Bytt hver 900 timer

HYDRAULISK BREMSESYSTEM

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
LHM +		

MANITOU MANISKOPISK MT/MTA MT 830 S CUMMINS



SMØREPUNKTER/NIPLER		
BRUK Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

TELESKOPISE TVERRSTOPPERPUTER		
BRUK Normal		KLIMA Moderat
PRODUKTANBEFALING 1 MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.