

MANITOU TELESKOPISE ARBEIDSPLATTFORMER 150 ATS SERIE 2 (INNTIL 2004)



MOTOR

Kapasitet: 5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

DIFFERENSIAL BAK

Kapasitet: 10 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

DIFFERENSIAL FORAN

Kapasitet: 10 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

NAVREDUKSJONER BAK

Kapasitet: 0,7 liter (hvert nav)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

NAVREDUKSJONER FORAN

Kapasitet: 0,8 liter (hvert nav)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

MANITOU TELESKOPISE ARBEIDSPLATTFORMER 150 ATS SERIE 2 (INNTIL 2004)

**OVERFØRINGSBOKS**

Kapasitet: 0,6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90**HYDRAULIKKSYSTEM**

Kapasitet: 75 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46**SMØREPUNKTER/NIPLER**

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2

Caliplex HD Grease EP 2**KJØLESYSTEM**

Kapasitet: 10 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF**DREIESKIVE TANNRINGGIR**

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Compound OGL

PRODUKTANBEFALING 2

Compound OGL EP 0/1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.