

MANITOU TELESKOPISE ARBEIDSPLATTFORMER 170 ATT PERKINS 903-27 (1998-2001)



MOTOR Perkins 903-27
Kapasitet: 5 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

DIFFERENSIAL BAK
Kapasitet: 9,5 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT		

DIFFERENSIAL FORAN
Kapasitet: 10 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT		

NAVREDUKSJONER BAK
Kapasitet: 0,8 liter (hvert nav)

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

NAVREDUKSJONER FORAN
Kapasitet: 0,8 liter (hvert nav)

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

MANITOU TELESKOPISE ARBEIDSPLATTFORMER 170 ATT PERKINS 903-27 (1998-2001)



OVERFØRINGSBOKS

Kapasitet: 0,6 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HYDRAULIKKSYSTEM

Kapasitet: 75 liter (Hydraulikkttank)

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

SMØREPUNKTER/NIPLER

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

KJØLESYSTEM

Kapasitet: 10 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

DREIESKIVE TANNRINGGIR

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Compound OGL	Compound OGL EP 0/1	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.