

MANITOU TELESKOPISE ARBEIDSPLATTFORMER 230 CTJ ISUZU A- 4JB1



MOTOR Isuzu 4JB1
Kapasitet: 8 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Sjekk hver 8 timer, bytt hver 500 timer

BRUK
Første service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Bytt hver 50 timer

HYDRAULIKKSYSTEM
Kapasitet: 150 liter (Hydraulikktank)

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 22

Bytt hver 1000 timer/ 12 måneder

ROTASJONSVIKLING BREMSESYSTEM
Kapasitet: 1,7 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Bytt hver 1000 timer

SMØREPUNKTER/NIPLER

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

MANITOU TELESKOPISE ARBEIDSPLATTFORMER 230 CTJ ISUZU A- 4JB1

**KJØLESYSTEM**

Kapasitet: 10,9 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Sjekk hver 8 timer, bytt hver 24 måneder***KJØREREDUKSJONSENHET**

Kapasitet: 2,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Bytt hver 1000 timer*

BRUK

Første service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Bytt hver 50 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.