

IVECO DAILY / TURBODAILY TURBODAILY 49.12 (1996-1999)



ENGINE 8140.43.37
Capacity: 7 litre, Filter Capacity: 1,1 litre

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 30	PRODUCT RECOMMENDATION 2 Multifleet SCD 40	
---	---	--

Change every 20000 km/ 12 months

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Bi-Turbo 15W-40	PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40
---	--	--

Change every 20000 km/ 12 months

USE Normal	CLIMATE Cold
----------------------	------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
---	--	--

Change every 20000 km/ 12 months

USE Normal	CLIMATE Arctic
----------------------	--------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
--	--	--

Change every 20000 km/ 12 months

DIFFERENTIAL REAR 4517
Capacity: 1,9 litre

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140	PRODUCT RECOMMENDATION 2 Unigear LS GL-3/GL-5 85W-140	
---	--	--

Check every 20000 km, change every 60000 km/ 12 months

USE Normal	CLIMATE Arctic
----------------------	--------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 20000 km, change every 60000 km/ 12 months

IVECO DAILY / TURBODAILY TURBODAILY

49.12 (1996-1999)



TRANSMISSION MANUAL 5/1

Capacity: 1,5 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km, change every 60000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

Capacity: 1,1 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 12 months

POWER STEERING ZF 8090

Capacity: 1,4 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	

Check every 20000 km/ 12 months

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MP Lithep Grease EP 2	

Check every 20000 km/ 12 months

IVECO DAILY / TURBODAILY TURBODAILY

49.12 (1996-1999)



COOLING SYSTEM

Capacity: 13 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 120000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.