

PRODUCT RECOMMENDATION

**UNIMOG (MB) 403, 406, 413, 416 U 900 (406),
U 1100 (416) (1970-1992)**



ENGINE Mercedes-Benz OM352
Capacity: 11 litre

USE Normal	CLIMATE Tropical
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 40		
---	--	--

Check every 200 hours, change every 400 hours

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
---	--	--

Check every 200 hours, change every 400 hours

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynt LSP 10W-40	PRODUCT RECOMMENDATION 2 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 3 Kroontrak Synth 10W-40
---	--	--

Check every 200 hours, change every 400 hours

USE Normal	CLIMATE Arctic
----------------------	--------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
--	--	--

Check every 200 hours, change every 400 hours

DIFFERENTIAL LOCK AIR OPERATED

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 HDX 20W-20		
--	--	--

Check every 12 months/ 1600 hours

DIFFERENTIAL FRONT
Capacity: 2,5 litre

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 100 hours, change every 1600 hours/ 12 months

PRODUCT RECOMMENDATION

**UNIMOG (MB) 403, 406, 413, 416 U 900 (406),
U 1100 (416) (1970-1992)**



DIFFERENTIAL REAR Capacity: 2,5 litre		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 100 hours, change every 1600 hours/ 12 months</i>		

HUB REDUCTIONS FRONT Capacity: 0,25 litre		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 100 hours, change every 1600 hours/ 12 months</i>		

HUB REDUCTIONS REAR Capacity: 0,25 litre		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 100 hours, change every 1600 hours/ 12 months</i>		

HYDRAULIC CLUTCH SYSTEM Capacity: 0,2 litre		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		
<i>Change every 12 months</i>		

PRODUCT RECOMMENDATION

**UNIMOG (MB) 403, 406, 413, 416 U 900 (406),
U 1100 (416) (1970-1992)**



HYDRAULIC SYSTEM

Capacity: 18 litre

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Perlus H 15		

Change every 2400 hours/ 24 months

HYDROSTATIC DRIVE

Capacity: 10,5 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	Perlus H 15	

Check every 600 hours, change every 1200 hours/ 12 months

POWER TAKE OFF

Capacity: 8 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 800 hours, change every 1600 hours/ 12 months

PRODUCT RECOMMENDATION

**UNIMOG (MB) 403, 406, 413, 416 U 900 (406),
U 1100 (416) (1970-1992)**



POWER TAKE OFF HOUSING

Capacity: 1,4 litre

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		

Check every 800 hours, change every 1600 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W		

Check every 800 hours, change every 1600 hours/ 12 months

TRANSMISSION MANUAL 20/8

Capacity: 6 litre

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		

Check every 800 hours, change every 1600 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W		

Check every 800 hours, change every 1600 hours/ 12 months

HYDRAULIC SYSTEM DIFFERENTIAL LOCK

Capacity: 0,3 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 10W	ATF-A	

Change every 1600 hours/ 12 months

PRODUCT RECOMMENDATION

**UNIMOG (MB) 403, 406, 413, 416 U 900 (406),
U 1100 (416) (1970-1992)**



FLUID CLUTCH

Capacity: 20 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 10W	Perlus H 15

Check every 600 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,8 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Drauliquid-S DOT 4

Change every 12 months

POWER STEERING

Capacity: 2,5 litre

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1
Multifleet SCD 30

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Multifleet SCD 10W

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1
ATF-A

Change every 2400 hours/ 24 months

PRODUCT RECOMMENDATION

**UNIMOG (MB) 403, 406, 413, 416 U 900 (406),
U 1100 (416) (1970-1992)**



GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2		

Check every 100 hours, change every 800 hours

COOLING SYSTEM

Capacity: 24 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 11		

Change every 36 months

AIR COMPRESSOR

Capacity: 0,1 litre

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40		

Change every 200 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30		

Change every 200 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynt LSP 10W-40	Kroontrak CVT 10W-40	Kroontrak Synth 10W-40

Change every 200 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W		

Change every 200 hours

PRODUCT RECOMMENDATION

**UNIMOG (MB) 403, 406, 413, 416 U 900 (406),
U 1100 (416) (1970-1992)**



STEERING BOX

Capacity: 0,6 litre

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
ATF-A		

Change every 2400 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.