

## Kroon-Oil Product recommendation

# Acura (USA / CAN) TLX TLX 3.5 AWD (2014 and after)

ENGINE, J35Y6

4,3 litre Capacity

0,3 litre Filter capacity

Recommended product

Presteza MSP 0W-20

Flexible (max), Change every 12 months

Good alternatives <u>Enersynth FE 0W-20</u>

Flexible (max), Change every 12 months

DIFFERENTIAL REAR

We are unable to give a standard recommendation for this component. Please

contact our service department.

**TRANSFERBOX** 

0,43 litre Capacity

Recommended product | SP G

**SP Gear 1011** 

Severe, Change every 48000 km

Good alternatives

<u>SP Gear 1011</u>

**SP Gear 1011** 

Severe, first change only, Change every 64000 km

SP Gear 1051

Severe, Change every 48000 km

SP Gear 1051

TRANSMISSION AUTOMATIC, 9/1

3,3 litre Capacity

Recommended product Good alternatives

SP Matic 4036

SP Matic 4036

Severe, Change every 48000 km

SP Matic 4036

Severe, first change only, Change every 64000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### HYDRAULIC BRAKE SYSTEM

Recommended product | Drauliquid DOT 3

Normal, Change every 36 months

COOLING SYSTEM 0,72 litre Capacity 8,4 litre Capacity

Recommended product | Coolant SP 12

#### AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

#### AIRCONDITIONING SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.