

ALFA ROMEO 156 932 156 2.5 V6 24V (2002-2005)



ENGINE AR 32405
Capacity: 6,4 litre

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Emperol 10W-40	PRODUCT RECOMMENDATION 2 Emperol Racing 10W-60	
--	---	--

Check every 500 km, change every 20000 km/ 12 months

USE Normal	CLIMATE Arctic
----------------------	--------------------------

PRODUCT RECOMMENDATION 1 Duranza LSP 5W-30	PRODUCT RECOMMENDATION 2 Asyntho 5W-30	
---	---	--

Check every 500 km, change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC Q-SYSTEM Aisin Warner 4/1

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 SP Matic 2032	PRODUCT RECOMMENDATION 2 ATF Almirol	
---	---	--

Check every 20000 km/ 12 months

TRANSAXLE MANUAL 6/1

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 SP Gear 1051	PRODUCT RECOMMENDATION 2 SP Gear 5015	PRODUCT RECOMMENDATION 3 Syngear 75W-90
--	--	--

Check every 80000 km/ 48 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Drauliquid-LV Super DOT 4	PRODUCT RECOMMENDATION 2 Drauliquid-S DOT 4	
---	--	--

Check every 500 km, change every 60000 km/ 24 months

ALFA ROMEO 156 932 156 2.5 V6 24V (2002-2005)



POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 500 km

COOLING SYSTEM

Capacity: 9,2 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Check every 500 km, change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.