



Kroon-Oil Product recommendation

Audi (EU) A3, S3 Cabriolet 8V7 A3 Cabriolet 1.8 TFSI (125 kW
(2014-2016))

Recommended product	ENGINE, CNSB <u>Presteza MSP 5W-30</u> Normal, Change every 15000 km/ 12 months
Good alternatives	<u>Helar SP LL-03 5W-30</u> Extended drain (max), Change every 30000 km/ 24 months <u>Helar 0W-40</u> Normal, Change every 15000 km/ 12 months <u>Emperol 5W-40</u> Normal, Change every 15000 km/ 12 months
Recommended product	HYDRAULIC ACTUATION GEARBOX <u>SP Fluid 3013</u>
Recommended product	TRANSAXLE SEMI-AUTOMATIC S TRONIC, 0D9 6/1 <u>SP Matic 2072</u>
Recommended product	HYDRAULIC ACTUATION CONVERTIBLE ROOF <u>SP Fluid 3013</u>
Recommended product	HYDRAULIC BRAKE/CLUTCH SYSTEM <u>Drauliquid-LV Super DOT 4</u> Normal, Change every 24 months
Recommended product	COOLING SYSTEM 0-0 litre Capacity <u>Coolant SP 13</u> Normal, Check every 30000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.