

VOLKSWAGEN (VW) (EU) TIGUAN AD1 TIGUAN 2.0 TSI (132 KW) 4MOTION (2016 AND AFTER)



ENGINE CZPA
Capacity: 5,7 litre (Service fill)

USE Preferred, flexible (max)	CLIMATE Moderate
---	----------------------------

PRODUCT RECOMMENDATION 1 Helar FE LL-04 0W-20		
--	--	--

Change every 30000 km/ 24 months

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Helar 0W-40	PRODUCT RECOMMENDATION 2 Emperol 5W-40	PRODUCT RECOMMENDATION 3 Asyntho 5W-30
---	---	---

Change every 15000 km/ 12 months

USE Alternative, flexible (max)	CLIMATE Moderate
---	----------------------------

PRODUCT RECOMMENDATION 1 Helar SP LL-03 5W-30		
--	--	--

Change every 30000 km/ 24 months

ANGLE GEARBOX / TRANSFERBOX
Capacity: 0,75-0,9 litre

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 SP Gear 1011		
--	--	--

DIFFERENTIAL REAR
Capacity: 0,95 litre

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 SP Gear 1011		
--	--	--

DIFFERENTIAL REAR AS OF PRODUCTION DATE 08-04-20 0CQ
Capacity: 0,95 litre

We are unable to give a standard recommendation for this component. Please contact our service department.

HALDEX-CLUTCH AS OF PRODUCTION DATE 08-04-2019
Capacity: 0,75 litre (Dry fill), Capacity: 0,65 litre (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

VOLKSWAGEN (VW) (EU) TIGUAN AD1 TIGUAN 2.0 TSI (132 KW) 4MOTION (2016 AND AFTER)



HALDEX-CLUTCH UP TO PRODUCTION DATE 08-04-2019

Capacity: 0,75 litre (Dry fill), Capacity: 0,65 litre (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE MANUAL 02Q 6/1

Capacity: 2,15-2,3 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

Check every 24 months/ 30000 km

TRANSAXLE SEMI-AUTOMATIC DSG 0DL (DQ500) 7/1

Capacity: 6,9-7,1 litre (Dry fill), Capacity: 5,5 litre (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

Change every 60000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 1,15 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

COOLING SYSTEM

Capacity: 0-0 litre (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 13		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.