

MERCEDES-BENZ (EU) 190 SL W121-190SL

190 SL R121 (1955-1963)



ENGINE M121 BII
Capacity: 4 litre, Filter capacity: 0,5 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 10W-30	Classic Monograde 30

Check every 3000 km, change every 6000 km

DIFFERENTIAL REAR
Capacity: 2,25 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Classic Gear MP 90

Check every 6000 km, change every 18000 km

TRANSMISSION MANUAL 4/1
Capacity: 1,4 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Classic ATF A

Check every 6000 km, change every 18000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0-0 litre (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Drauliquid DOT 3

Check every 3000 km

COOLING SYSTEM
Capacity: 10 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Coolant -38 Organic NF	Coolant -26

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) 190 SL W121-190SL
190 SL R121 (1955-1963)



STEERING BOX

Capacity: 0,3 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

Check every 18000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.