

# VOLVO MOTOR GRADERS G G930 (2007 AND AFTER)



**ENGINE** Volvo D7E Stage IIIA/Tier 3  
Capacity: 21,5 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak Super 15W-30</b>

*Change every 500 hours*

**DIFFERENTIAL REAR**  
Capacity: 22,7 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 95 litre (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Change every 2000 hours*

**TANDEM DRIVE**  
Capacity: 100 litre (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 1500 hours*

**TRANSMISSION**  
Capacity: 61 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF Almirol</b>		

*Change every 1000 hours*

# VOLVO MOTOR GRADERS G G930 (2007 AND AFTER)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Labora Grease</b>	<b>MP Lithep Grease EP 2</b>	

## COOLING SYSTEM

Capacity: 31 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 12</b>		

*Check every 8 hours, change every 48 months/ 6000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*