

# ALFA ROMEO 4C 960 / 961 4C 1.750 TBI (2013 AND AFTER)



## ENGINE 960A1000

Capacity: 5,8 litre (Service fill), Filter Capacity: 0,4 litre

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**Specialsynth MSP 5W-40**

*Change every 20000 km/ 12 months*

## HYDRAULIC ACTUATION GEARBOX

Capacity: 1,45 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Fluid 3023**

*Check every 20000 km/ 12 months*

## TRANSAXLE SEMI-AUTOMATIC TCT 6/1

Capacity: 1,9 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

*Check every 20000 km/ 12 months*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Change every 40000 km/ 24 months*

## COOLING SYSTEM

Capacity: 10,6 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 12**

*Check every 20000 km/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is*

PRODUCT RECOMMENDATION

# ALFA ROMEO 4C 960 / 961 4C 1.750 TBI (2013 AND AFTER)



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*