



## Kroon-Oil Product recommendation

Alfa Romeo 159 939 159 3.2 JTS (2008-2010)

Recommended product	<p>ENGINE, 939A000 5,4 litre Capacity <u>Emperol 5W-40</u> Flexible (max), Check every 3000 km Flexible (max), Change every 30000 km/ 24 months</p>
Recommended product	<p>TRANSAXLE MANUAL, 6/1 2,8 litre Capacity <u>SP Gear 1051</u></p>
Recommended product	<p>HYDRAULIC BRAKE/CLUTCH SYSTEM ABS <u>Drauliquid-LV Super DOT 4</u> Normal, Change every 30000 km/ 24 months</p>
Good alternatives	<p><u>Drauliquid-S DOT 4</u> Normal, Change every 30000 km/ 24 months</p>
Recommended product	<p>POWER STEERING <u>SP Fluid 3013</u> Normal, Check every 30000 km/ 24 months</p>
	<p>GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE We are unable to give a standard recommendation for this component. Please contact our service department.</p>
Recommended product	<p>GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE 151 grams Capacity <u>MoS2 Grease EP 2</u></p>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product

#### COOLING SYSTEM

10,3 litre Capacity

Coolant SP 12

Normal, Check every 30000 km/ 24 months

Good alternatives

Coolant -38 Organic NF

Normal, Check every 30000 km/ 24 months

#### AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.