

AHLMANN WHEELED LOADERS AL AL 7 (1985-1988)



ENGINE Capacity: 7,5 litre		
USE Normal		CLIMATE Moderate

PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40	
---	---	--

Change every 100 hours

USE Initial service		CLIMATE Moderate
------------------------	--	---------------------

PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40	
---	---	--

Change every 10 hours

DIFFERENTIAL FRONT Capacity: 6,5 litre		
USE Normal		CLIMATE Moderate

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
---	--	--

Change every 1000 hours

USE Initial service		CLIMATE Moderate
------------------------	--	---------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
---	--	--

Change every 50 hours

DIFFERENTIAL REAR Capacity: 8,5 litre		
USE Normal		CLIMATE Moderate

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
---	--	--

Change every 1000 hours

USE Initial service		CLIMATE Moderate
------------------------	--	---------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
---	--	--

Change every 50 hours

AHLMANN WHEELED LOADERS AL AL 7 (1985-1988)



HUB REDUCTIONS FRONT

Capacity: 0,7 litre (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 50 hours

HUB REDUCTIONS REAR

Capacity: 0,7 litre (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 45 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus H 46	Perlus AF 46

Change every 1000 hours

AHLMANN WHEELED LOADERS AL AL 7 (1985-1988)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MP Lithep Grease EP 2	

COOLING SYSTEM

Capacity: 12 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant -38 Organic NF	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.