

FORD 10 4610 (1981-1989)



| ENGINE Capacity: 6,6 litre | | |
|---|------------------------------|--|
| USE | CLIMATE | |
| Normal | Tropical | |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| <i>Check every 10 hours, change every 300 hours</i> | | |
| USE | CLIMATE | |
| Normal | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Kroontrak Super 10W-30 | Multifleet SCD 20W-20 | |
| <i>Check every 10 hours, change every 300 hours</i> | | |
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak Super 15W-30 | | |
| <i>Check every 10 hours, change every 300 hours</i> | | |
| USE | CLIMATE | |
| Normal | Cold | |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| <i>Check every 10 hours, change every 300 hours</i> | | |

| DIFFERENTIAL FRONT (4x4) Capacity: 6 litre | | |
|--|-------------------------------|-----------------------------|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT | Kroontrak Super 10W-30 | Gearlube GL-5 80W-90 |
| <i>Check every 50 hours, change every 1200 hours</i> | | |

| DIFFERENTIAL REAR/HYDRAULIC SYSTEM Capacity: 45,7 litre | | |
|---|-------------------------------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT | Kroontrak Super 10W-30 | |
| <i>Check every 50 hours, change every 1200 hours</i> | | |

FORD 10 4610 (1981-1989)



HUB REDUCTIONS FRONT (4x4)

Capacity: 1,5 litre

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|--------------------------|---------------------------|------------------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT | Gearlube LS 80W-90 | Unigear HS GL-3/GL-5 80W-90 |

Check every 50 hours, change every 1200 hours

TRANSMISSION MANUAL 8/2

Capacity: 9,4 litre

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|--------------------------|-------------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT | Kroontrak Super 10W-30 | |

Check every 300 hours, change every 1200 hours

TRANSMISSION MANUAL 8/4

Capacity: 12 litre

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|--------------------------|-------------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT | Kroontrak Super 10W-30 | |

Check every 300 hours, change every 1200 hours

POWER STEERING

Capacity: 2,2 litre

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|-------------------------------|----------------------------------|---------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak Synth 10W-40 | Agrifluid Synth XHP Ultra | Agrifluid Synth WB |

Check every 300 hours, change every 1200 hours/ 12 months

GREASE POINTS/NIPPLES

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Labora Grease | MoS2 Grease EP 2 | |

Check every 50 hours

FORD 10 4610 (1981-1989)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Labora Grease | MoS2 Grease EP 2 | |

Check every 600 hours

COOLING SYSTEM

Capacity: 10,4 litre

| | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 12 | Coolant -26 | |

Check every 10 hours, change every 2400 hours/ 24 months

BELT PULLEY

Capacity: 1,13 litre

| | | |
|--------------------------|-------------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT | Kroontrak Super 10W-30 | |

Check every 50 hours, change every 1200 hours

STEERING BOX

Capacity: 0,64 litre

| | | |
|-------------------------------|----------------------------------|---------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak Synth 10W-40 | Agrifluid Synth XHP Ultra | Agrifluid Synth WB |

Check every 600 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.