

INTERNATIONAL HARVESTER 85 585, 585 XL (1981-1985)



ENGINE D-206
Capacity: 8,5 litre

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 30	Multifleet SCD 30	

Check every 10 hours, change every 200 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	HDX 20W-20	Multifleet SCD 20W-20

Check every 10 hours, change every 200 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Kroontrak Super 10W-30		

Check every 10 hours, change every 200 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 10W	Multifleet SCD 10W	

Check every 10 hours, change every 200 hours

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid IH	Agrifluid HT-Plus	

Check every 10 hours

TRANSAXLE/HYDRAULIC SYSTEM 8/4
Capacity: 34 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid IH	Agrifluid HT-Plus	

Check every 10 hours, change every 800 hours

INTERNATIONAL HARVESTER 85 585, 585 XL (1981-1985)



GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MP Lithep Grease EP 2	
<i>Check every 10 hours</i>		

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MP Lithep Grease EP 2	
<i>Change every 800 hours</i>		

COOLING SYSTEM		
Capacity: 13,7 litre		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Check every 10 hours</i>		

BELT PULLEY		
Capacity: 0,5 litre		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid IH	Agrifluid HT-Plus	
<i>Check every 800 hours</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.