

NEW HOLLAND TM TM 165 (2000-2002)



ENGINE NH 675/WW Capacity: 19 litre		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Kroontrak Super 15W-30	PRODUCT RECOMMENDATION 3 Kroontrak Super 10W-30
<i>Check every 10 hours, change every 300 hours</i>		

DIFFERENTIAL FRONT Capacity: 14 litre		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT	PRODUCT RECOMMENDATION 2 Kroontrak Super 10W-30	
<i>Check every 300 hours, change every 1200 hours/ 12 months</i>		

HUB REDUCTIONS FRONT Capacity: 2,15 litre		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT	PRODUCT RECOMMENDATION 2 Kroontrak Super 10W-30	
<i>Check every 300 hours, change every 1200 hours/ 12 months</i>		

HYDRAULIC BRAKE SYSTEM		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 LHM +		

TRANSAXLE/HYDRAULIC SYSTEM PowerCommand 17/6 Capacity: 100 litre		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT	PRODUCT RECOMMENDATION 2 Kroontrak Super 10W-30	
<i>Check every 300 hours, change every 1200 hours/ 12 months</i>		



NEW HOLLAND TM TM 165 (2000-2002)



TRANSAXLE/HYDRAULIC SYSTEM Range Command 17/6

Capacity: 90 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT	Kroontrak Super 10W-30	

Check every 300 hours, change every 1200 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Change every 50 hours

COOLING SYSTEM

Capacity: 23,5 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12		

Check every 10 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.