



Kroon-Oil Product recommendation

Audi (EU) A6, S6 4A A6 2.8 V6 quattro (1994-1997)

Recommended product	ENGINE, AAH 5 litre Capacity <u>Presteza MSP 5W-30</u> Normal, Change every 15000 km/ 12 months
Good alternatives	<u>Helar SP LL-03 5W-30</u> Normal, Change every 15000 km/ 12 months <u>Helar 0W-40</u> Normal, Change every 15000 km/ 12 months <u>Emperol 5W-40</u> Normal, Change every 15000 km/ 12 months <u>Emperol 10W-40</u> Normal, Change every 15000 km/ 12 months
Recommended product	DIFFERENTIAL FROM AUTOMATIC 1 litre Capacity <u>SP Gear 1011</u> Normal, Check every 15000 km/ 12 months
Recommended product	DIFFERENTIAL REAR 1,7 litre Capacity <u>Gearlube GL-5 80W-90</u> Normal, Check every 15000 km/ 12 months
Recommended product	TRANSAXLE MANUAL, 5/1 2,75 litre Capacity <u>SP Gear 1011</u> Normal, Check every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product TRANSAXLE MANUAL/TRANSFERBOX, 5/1
2,75 litre Capacity
SP Gear 1011
Normal, Check every 15000 km/ 12 months

Recommended product TRANSMISSION AUTOMATIC, 4/1
2,7 litre Capacity
SP Matic 4026
Normal, Check every 30000 km/ 12 months
Normal, Change every 60000 km/ 48 months

Good alternatives SP Matic 2032
Normal, Check every 30000 km/ 12 months
Normal, Change every 60000 km/ 48 months

Recommended product HYDRAULIC BRAKE/CLUTCH SYSTEM
Drauliquid-LV Super DOT 4
Normal, Change every 24 months

Good alternatives Drauliquid-S DOT 4
Normal, Change every 24 months

Recommended product HYDRAULIC SYSTEM POWER STEERING/LEVELLING
2,5 litre Capacity
SP Fluid 3013

Recommended product POWER STEERING
1,1 litre Capacity
SP Fluid 3013

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product

COOLING SYSTEM

11 litre Capacity

Coolant -38 Organic NF

Normal, Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.