



Kroon-Oil Product recommendation

Atlas GmbH Tracked excavators 340NLC (2010 and after)

Recommended product

ENGINE, DEUTZ TCD 2013 L06 2V

21 litre Capacity

Dieselfleet CD+ 15W-40

Normal, Change every 500 hours

Good alternatives

Dieselfleet CD+ 15W-40

Initial service, Change every 50 hours

Multifleet SHPD 10W-40

Alternative (acceptable), Change every 250 hours

HYDRAULIC SYSTEM

505 litre Capacity

Recommended product

Multifleet SCD 10W

Normal, Change every 3000 hours

Good alternatives

Multifleet SCD 20W-20

Normal, Change every 3000 hours

SWING REDUCTION UNIT

Recommended product

Gearlube Racing 75W-140

Normal, Change every 2000 hours

Good alternatives

Gearlube LS 80W-90

Normal, Change every 2000 hours

TRANSMISSION

Recommended product

Unigear HS GL-3/GL-5 80W-90

Normal, Change every 2000 hours

Good alternatives

Unigear HS GL-3/GL-5 80W-90

Initial service, Change every 500 hours

Gearlube GL-5 80W-90

Normal, Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product TRAVEL REDUCTION UNIT
Gearlube Racing 75W-140
Normal, Change every 2000 hours

Good alternatives Gearlube LS 80W-90
Normal, Change every 2000 hours

Recommended product GREASE POINTS/NIPPLES OTHERS
MoS2 Grease EP 2

Recommended product COOLING SYSTEM
42 litre Capacity
Coolant SP 12
Normal, Change every 2000 hours

SWING RING GEAR TEETH

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.