

ALFA ROMEO 145 930 145 TD (1994-1999)



ENGINE Capacity: 5 litre		
USE	CLIMATE	
Normal	Moderate	

PRODUCT RECOMMENDATION 1		
Emperol 10W-40		

Check every 500 km, change every 20000 km/ 12 months

USE	CLIMATE	
Normal	Arctic	

PRODUCT RECOMMENDATION 1		
Emperol 5W-40		

Check every 500 km, change every 20000 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 2 litre		
--	--	--

USE	CLIMATE	
Normal	Moderate	

PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W		

Check every 40000 km, change every 120000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM		
--------------------------------------	--	--

USE	CLIMATE	
Normal	Moderate	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 500 km, change every 12 months

POWER STEERING		
-----------------------	--	--

USE	CLIMATE	
Normal	Moderate	

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 500 km

ALFA ROMEO 145 930 145 TD (1994-1999)



COOLING SYSTEM

Capacity: 8,9 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Check every 500 km, change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.