



Kroon-Oil Product recommendation

Audi (EU) A3, S3, RS3 8P A3 3.2 quattro (184 kW) (2003-2005)

Recommended product	ENGINE, BDB, BMJ 5,5 litre Capacity <u>Presteza MSP 5W-30</u> Normal, Change every 15000 km/ 12 months
Good alternatives	<u>Helar SP LL-03 5W-30</u> Normal, Change every 15000 km/ 12 months <u>Helar SP LL-03 5W-30</u> Extended drain (max), Change every 30000 km/ 24 months <u>Specialsynth MSP 5W-40</u> Normal, Change every 15000 km/ 12 months <u>Helar 0W-40</u> Normal, Change every 15000 km/ 12 months
Recommended product	BEVEL GEAR 0,9 litre Capacity <u>SP Gear 1011</u>
Recommended product	DIFFERENTIAL REAR 1 litre Capacity <u>SP Gear 1011</u>
	HALDEX-CLUTCH We are unable to give a standard recommendation for this component. Please contact our service department.
Recommended product	TRANSAXLE MANUAL, 02Q 6/1 2,3 litre Capacity <u>SP Gear 1051</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product	<p>TRANSAXLE SEMI-AUTOMATIC, DSG 02E (DQ250) 6/1 7,2 litre Capacity 6 litre Capacity <u>SP Matic 2072</u> Normal, Change every 60000 km</p>
Recommended product	<p>HYDRAULIC BRAKE SYSTEM <u>Drauliquid-LV Super DOT 4</u> Normal, Change every 24 months</p>
Recommended product	<p>COOLING SYSTEM 0-0 litre Capacity <u>Coolant SP 13</u> Normal, Check every 30000 km/ 24 months</p>
Good alternatives	<p><u>Coolant SP 12</u> Normal, Check every 30000 km/ 24 months</p>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.