



## Kroon-Oil Product recommendation

Audi (EU) A3, S3, RS3 8P S3 2.0 TFSI quattro (195 kW) (20  
9-2013)

### ENGINE, CDLA, CDMA

Remarks: Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!

Recommended product

Presteza MSP 5W-30

Normal, Change every 15000 km/ 12 months

Good alternatives

Helar SP LL-03 5W-30

Extended drain (max), Change every 30000 km/ 24 months

Helar 0W-40

Normal, Change every 15000 km/ 12 months

Emperol 5W-40

Normal, Change every 15000 km/ 12 months

### BEVEL GEAR / TRANSFERBOX

0,9 litre Capacity

Recommended product

SP Gear 1011

Normal, Check every 48 months/ 60000 km

### DIFFERENTIAL REAR

1 litre Capacity

Recommended product

SP Gear 1011

Normal, Check every 48 months/ 60000 km

### HALDEX-CLUTCH

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product	<p>TRANSAXLE MANUAL, 02Q 6/1  2,3 litre Capacity  <u>SP Gear 1051</u>  Normal, Check every 48 months/ 60000 km</p>
Recommended product	<p>TRANSAXLE SEMI-AUTOMATIC, DSG 02E (DQ250) 6/1  6,9 litre Capacity  <u>SP Matic 2072</u>  Normal, Change every 60000 km</p>
Recommended product	<p>HYDRAULIC BRAKE/CLUTCH SYSTEM ABS  0-0 litre Capacity  <u>Drauliquid-LV Super DOT 4</u>  Normal, Change every 24 months</p>
Recommended product	<p>COOLING SYSTEM  0-0 litre Capacity  <u>Coolant SP 13</u>  Normal, Check every 48 months/ 60000 km</p>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.