

# ATLAS GMBH TRACKED EXCAVATORS

## 210NLC (2010 AND AFTER)



**ENGINE** Cummins QSB6.7  
Capacity: 20 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Armado Synth 5W-30</b>	<b>Dieselfleet CD+ 15W-40</b>

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

**TRANSMISSION** Powershift

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>Multifleet SCD 20W-20</b>	

*Change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 2000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>Multifleet SCD 20W-20</b>	

*Change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 500 hours*

# ATLAS GMBH TRACKED EXCAVATORS

## 210NLC (2010 AND AFTER)



### HYDRAULIC SYSTEM

Capacity: 216 liter (Hydraulic tank), Capacity: 290 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1  
**Multifleet SCD 20W-20**

*Change every 3000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1  
**Multifleet SCD 10W**

*Change every 3000 hours*

### GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1  
**MoS2 Grease EP 2**

### COOLING SYSTEM

Capacity: 42 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1  
**Coolant SP 15**

PRODUCT RECOMMENDATION 2  
**Coolant SP 15+**

PRODUCT RECOMMENDATION 3  
**Coolant SP 12**

### SWING REDUCTION UNIT

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1  
**Gearlube Racing 75W-140**

*Change every 2000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1  
**Gearlube LS 80W-90**

*Change every 2000 hours*

# ATLAS GMBH TRACKED EXCAVATORS

## 210NLC (2010 AND AFTER)



### SWING RING GEAR TEETH

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Compound OGL EP 0/1</b>		

### TRAVEL REDUCTION UNIT

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 2000 hours*

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*