

ATLAS GMBH WHEELED EXCAVATORS

1304 135M301854 ->



ENGINE

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL HUB REDUCTIONS

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 1000 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 500 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

ATLAS GMBH WHEELED EXCAVATORS

1304 135M301854 ->



TRANSFERBOX

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 1000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 1000 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 500 hours*

HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Change every 3000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 3000 hours*

ATLAS GMBH WHEELED EXCAVATORS**1304 135M301854 ->****GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

*Change every 2000 hours***SWING RING GEAR TEETH**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Compound OGL EP 0/1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.