PRODUCT RECOMMENDATION

AUSA WHEELED DUMPERS D 150 AHG KUBOTA D1105 (2006 AND AFTER)

ENGINE Kubota D1105
Capacity: 5,1 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SHPD 20W-50**

Change every 200 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	**Synfleet SHPD 10W-40**

Change every 200 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SHPD 20W-50**

Change every 50 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	**Synfleet SHPD 10W-40**

Change every 50 hours

DIFFERENTIAL FRONT
Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 40 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

AUSA WHEELED DUMPERS D 150 AHG KUBOTA D1105 (2006 AND AFTER)

DIFFERENTIAL REAR
Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 40 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

TRANSFERBOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 40 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 30 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Perlus AF 100		

Check every 40 hours, change every 800 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	**Perlus AF 68**	

Check every 40 hours, change every 800 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

AUSA WHEELED DUMPERS D 150 AHG KUBOTA D1105 (2006 AND AFTER)

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 46	**Perlus AF 46**	
Check every 40 hours, change every 800 hours		

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Perlus AF 100		
Change every 50 hours		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 68	**Perlus AF 68**	
Change every 50 hours		

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 46	**Perlus AF 46**	
Change every 50 hours		

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 11	**Coolant -38 Organic NF**	**Coolant -26**
Check every 40 hours, change every 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367