

# AUSA WHEELED DUMPERS D 350 AHG

## KUBOTA V2403-M (2008 AND AFTER)



**ENGINE** Kubota V2403-M  
Capacity: 9,5 liter

USE  
Normal

CLIMATE  
Mediterranean

PRODUCT RECOMMENDATION 1  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3  
**Multifleet SHPD 20W-50**

*Change every 150 hours*

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Synfleet SHPD 10W-40**

*Change every 150 hours*

USE  
Initial service

CLIMATE  
Mediterranean

PRODUCT RECOMMENDATION 1  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3  
**Multifleet SHPD 20W-50**

*Change every 50 hours*

USE  
Initial service

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Synfleet SHPD 10W-40**

*Change every 50 hours*

**DIFFERENTIAL FRONT** Dana  
Capacity: 4,1 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube LS 80W-90**

*Check every 40 hours, change every 900 hours*

USE  
Initial service

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube LS 80W-90**

*Change every 50 hours*

# AUSA WHEELED DUMPERS D 350 AHG

## KUBOTA V2403-M (2008 AND AFTER)



### DIFFERENTIAL FRONT Newage

Capacity: 6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Agrifluid HT</b>      |  |  |

Check every 40 hours, change every 12 months/ 900 hours

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Agrifluid HT</b>      |  |  |

Change every 50 hours

### DIFFERENTIAL REAR Dana

Capacity: 4,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Check every 40 hours, change every 900 hours

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Change every 50 hours

### DIFFERENTIAL REAR Newage

Capacity: 3,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Agrifluid HT</b>      |  |  |

Check every 40 hours, change every 12 months/ 900 hours

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Agrifluid HT</b>      |  |  |

Change every 50 hours

# AUSA WHEELED DUMPERS D 350 AHG

## KUBOTA V2403-M (2008 AND AFTER)



### HUB REDUCTIONS Dana

Capacity: 0,35 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 40 hours, change every 900 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 50 hours*

### TRANSFERBOX Dana

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 40 hours, change every 12 months/ 900 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 40 hours*

### TRANSFERBOX Newage

Capacity: 0,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT***Check every 40 hours, change every 12 months/ 900 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT***Change every 50 hours*

# AUSA WHEELED DUMPERS D 350 AHG

## KUBOTA V2403-M (2008 AND AFTER)

**HYDRAULIC SYSTEM**

Capacity: 45 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus AF 100</b>     |  |  |

*Check every 40 hours, change every 900 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
| <b>Perlus H 68</b>       | <b>Perlus AF 68</b>      |  |

*Check every 40 hours, change every 900 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |  |

*Check every 40 hours, change every 900 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Tropical |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus AF 100</b>     |  |  |

*Change every 50 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
| <b>Perlus H 68</b>       | <b>Perlus AF 68</b>      |  |

*Change every 50 hours*

| USE             | CLIMATE |
|-----------------|---------|
| Initial service | Cold    |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |  |

*Change every 50 hours*

# AUSA WHEELED DUMPERS D 350 AHG

## KUBOTA V2403-M (2008 AND AFTER)



### HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>LHM +</b>             | <b>Perlus H 32</b>       | <b>Perlus AF 32</b>      |

*Check every 40 hours, change every 900 hours*

### GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM

Capacity: 7,5 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 40 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*