

# AUSA WHEELED DUMPERS D 900 AP

## KUBOTA V3800-DI-T (2008 AND AFTER)



**ENGINE** Kubota V3800-DI-T  
Capacity: 11,95 liter

USE  
Normal

CLIMATE  
Mediterranean

PRODUCT RECOMMENDATION 1  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3  
**Multifleet SHPD 20W-50**

*Change every 250 hours/ 12 months*

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Synfleet SHPD 10W-40**

*Change every 250 hours/ 12 months*

USE  
Initial service

CLIMATE  
Mediterranean

PRODUCT RECOMMENDATION 1  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3  
**Multifleet SHPD 20W-50**

*Change every 50 hours*

USE  
Initial service

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Synfleet SHPD 10W-40**

*Change every 50 hours*

**DIFFERENTIAL FRONT**  
Capacity: 11,37 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrifluid HT**

*Check every 40 hours, change every 12 months/ 750 hours*

**DIFFERENTIAL REAR**  
Capacity: 11,37 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrifluid HT**

*Check every 40 hours, change every 12 months/ 750 hours*

# AUSA WHEELED DUMPERS D 900 AP

## KUBOTA V3800-DI-T (2008 AND AFTER)



### POWERSHUTTLE AND CONVERTER 4/4

Capacity: 11,95 liter

| USE                         |                           | CLIMATE                  |
|-----------------------------|---------------------------|--------------------------|
| Normal                      |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SCD 10W</b> | <b>ATF Dexron II-D</b>   |

Check every 40 hours, change every 750 hours

| USE                         |                           | CLIMATE                  |
|-----------------------------|---------------------------|--------------------------|
| Initial service             |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SCD 10W</b> | <b>ATF Dexron II-D</b>   |

Change every 50 hours

### TRANSFERBOX

Capacity: 1,45 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 40 hours, change every 12 months/ 750 hours

### HYDRAULIC SYSTEM

Capacity: 50 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

Check every 40 hours, change every 1000 hours

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Initial service          |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

Change every 50 hours

# AUSA WHEELED DUMPERS D 900 AP

## KUBOTA V3800-DI-T (2008 AND AFTER)



### HYDRAULIC BRAKE SYSTEM

Capacity: 0,95 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>LHM +</b>             | <b>Perlus H 32</b>       | <b>Perlus AF 32</b>      |

Check every 40 hours, change every 750 hours

### GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM

Capacity: 9 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

Check every 40 hours, change every 24 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*