

## AUSA REACH TRUCKS TAURULIFT T133H



**ENGINE** Kubota D1105  
Capacity: 5,1 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SHPD 20W-50</b> |

*Change every 200 hours*

| USE                         |                             | CLIMATE                     |
|-----------------------------|-----------------------------|-----------------------------|
| Normal                      |                             | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Change every 200 hours*

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Initial service               |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SHPD 20W-50</b> |

*Change every 50 hours*

| USE                         |                             | CLIMATE                     |
|-----------------------------|-----------------------------|-----------------------------|
| Initial service             |                             | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Change every 50 hours*

**DIFFERENTIAL FRONT**  
Capacity: 1,6 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 200 hours, change every 1000 hours/ 12 months*

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Initial service             |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 50 hours*

## AUSA REACH TRUCKS TAURULIFT T133H

**HYDRAULIC SYSTEM**

Capacity: 32 liter (Hydraulic tank)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Tropical |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 68</b>       |  |          |

*Check every 10 hours, change every 1000 hours*

| USE                       |                          | CLIMATE       |
|---------------------------|--------------------------|---------------|
| Normal                    |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |               |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       |               |

*Check every 10 hours, change every 1000 hours*

| USE                       |                          | CLIMATE |
|---------------------------|--------------------------|---------|
| Normal                    |                          | Cold    |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |         |
| <b>Perlus Biosynth 32</b> | <b>Perlus H 32</b>       |         |

*Check every 10 hours, change every 1000 hours***HYDRAULIC SYSTEM BRAKING & INCHING**

Capacity: 1 liter

| USE                         |                                  | CLIMATE                     |
|-----------------------------|----------------------------------|-----------------------------|
| Normal                      |                                  | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> |

*Check every 40 hours, change every 1000 hours***GREASE POINTS/NIPPLES**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Change every 40 hours***COOLING SYSTEM**

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Change every 24 months**The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.*

# AUSA REACH TRUCKS TAURULIFT T133H



*Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*