PRODUCT RECOMMENDATION

AUSA MULTITASK BD120ML PERKINS (TILL 2010)

ENGINE Perkins
Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		

Change every 150 hours

DIFFERENTIAL REAR
Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 40 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

HUB REDUCTIONS REAR
Capacity: 0,25 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 40 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

AUSA MULTITASK BD120ML PERKINS (TILL 2010)

TRANSAXLE FRONT
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 40 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	**Perlus AF 68**	

Check every 40 hours, change every 1000 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Change every 600 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367